SOFTWARE ARCHITECTURE AND DESIGN PATTERN

<u>UNIT-III</u>

<u>PATTERN</u>: <u>PATTERN DESCRIPTION</u>

Software patterns are reusable solutions to recurring problems that occur during software development.

In general, a pattern has four essential elements:

The pattern name is a handle we can use to describe a design problem, its solutions, and consequences in a word or two. Naming a pattern immediately increases our design vocabulary. It lets us design a thigher level of abstraction. Having a vocabulary for patterns lets us talk about them with our colleagues, in our documentation, and even to ourselves. It makes it easier to think about designs and to communicate the mand their trade- offs to others. Finding good names has been one of the hardest parts of developing our catalog.

Theproblem describes when to apply the pattern. It explains the problem and its context. It might describes pecific design problems such as how to represent algorithms as objects. It might describe classorobjects tructures that are symptomatic of an inflexible design. Some times the problem will include a list of conditions that must be met be fore it makes sense to apply the pattern.

The solution describes the elements that make up the design, their relationships, responsibilities, and collaborations. The solution doesn't describe a particular concreted esign or implementation, because a patternislike a template that can be applied in many different situations. Instead, the pattern provides an abstract description of a design problem and how a general arrangement of elements (classes and objects in our case) solves it.

The consequences are the results and trade-offs of applying the pattern .Though consequences are often unvoiced when we describe design decisions ,theyare critical for evaluating designal ternatives and for understanding the costs and benefits of applying the pattern. The consequences for software often concerns pace and time trade-offs. They may address language and implementation issues as well. Since reuse is often a factor in object- oriented design, the consequences of a pattern include its impact on a system's flexibility, extensibility, or portability. Listing the secons equences explicitly helpsyou understand and evaluate them.

Organizing the Catalog

Design patterns vary in their granularity and level of abstraction. Because there are many designpatterns, we need away to organize them. This section classifies design patterns so that we can refer to families of related patterns. The classification helps you learn the patterns in the catalog faster, and it can direct efforts to find new patterns as well.

We classify design patterns by two criteria.

The first criterion, called purpose, reflects what a pattern does. Patterns can have either creational ,structural , or behavioral purpose. Creational patterns concern the process of objectcreation.Structuralpatternsdealwiththecompositionofclassesorobjects.Behavioral patternscharacterizethewaysinwhichclassesorobjectsinteractanddistributeresponsibility.

The second criterion, called scope ,specifies whether the pattern applies primarily to classes or to objects. Class patterns deal with relationships between classes and their subclasses. These relationships are established through inheritance, so they are static -fixed at compile-time. Object patterns deal with object relationships, which can be changed

atrun-timeandaremoredynamic. Almostallpatternsuseinheritancetosomeextent. So the only patterns labeled "class patterns" are those that focus on class relationships. Note that mostpatternsare in the Objectscope.

Purpose

| | | Creational | Structural | Behavioural |
|-------|--------|--|---|---|
| Scope | Class | FactoryMethod | Adapter | Interpreter Template Method |
| | Object | AbstractFactory Builder Prototype Singleton | Adapter Bridge Composite Decorator Facade Flyweight Proxy | Chain of Responsibility Command Iterator Mediator Memento Observer State Strategy Visitor |

How Design Patterns Solve Design Problems

Design patterns solve many of the day-to-day problems object-oriented designers face, and in many different ways. Here are several of these problems and how design patterns solve them.

Finding Appropriate Objects

Object-orientedprogramsaremadeupofobjects.Anobjectpackagesbothdataandthe proceduresthatoperateonthatdata.Theproceduresaretypicallycalledmethods oroperations. An object performs an operation when it receives a request (or message) from a client.

Requests are the only way to get an object to execute an operation. Operations are the onlywaytochangeanobject's internal data. Because of these restrictions, the object's internal state is said to be encapsulated; it cannot be accessed directly, and its representation is invisible from outside the object.

Determining Object Granularity

Objects canvary tremendously insize and number. They can represent everything down to the hardware or all the way up to entire applications. How dowed ecide what should be an object?

Design patterns address this issue as well. The Facade pattern describes how to represent complete subsystems as objects, and the Flyweight pattern describes how to support huge numbers of objects at the finest granularities .Other design patterns describe specific ways of decomposing an object into smaller objects. Abstract Factory and Builder yield objects whose only responsibilities are creating other objects. Visitor and Command yield objects whose only responsibilities are to implement a request on another objector group of objects

Specifying Object Interfaces

Every operation declared by an object specifies the operation's name, the objects it takes as parameters, and the operation's return value. This is known as the operation's signature. Thesetofallsignatures defined by an object's operations is called the interface to the object. An object's interface characterizes the complete set of requests that can be sent to the object. Any request that matches a signature in the object's interface may be sent to the object. Specifying Object Implementations

Sofarwe'vesaidlittleabouthowweactuallydefineanobject.Anobject'simplementationis definedbyitsclass.Theclassspecifiestheobject'sinternaldataandrepresentationanddefines theoperationstheobjectcanperform.

HowtoSelectaDesignPattern

Withmorethan20designpatternsinthecatalogtochoosefrom,itmightbehardtopfindtheone thataddressesaparticulardesignproblem,especiallyifthecatalogisnewandunfamiliarto you. Here are several different approaches to finding the design pattern that's right for your problem:

1. Consider how design patterns solve design problems. Designpatternshelpyoufindappropriateobjects,determineobjectgranularity,specify object interfaces, and several other ways in which design patterns solve design problems.Referringtothese discussionscanhelpguideyoursearchfortheright pattern.

- 2. ScanIntentsections.theIntentsectionsfromallthepatternsin the catalog. Read through each pattern's intent to find one or more that sound relevanttoyourproblem.Youcanusetheclassificationschemetonarrowyoursearch.
- 3. Study how patterns interrelate .Relationships betweendesign patternsgraphically.Studyingtheserelationshipscanhelpdirectyoutotherightpattern orgroupofpatterns
- 4. Studypatternsoflikepurpose. The cataloghasthree chapters, one for creational patterns, another for structural patterns, and a third for behavioral patterns. Each chapter startsoff with introductory comments on the patterns and concludes with a section that compares and contrasts them. These sections give your insight into the similarities and differences between patterns of like purpose.
- 5. Examineacauseofredesign.Lookatthecausesofredesignstartingto seeifyourprobleminvolvesoneormoreofthem.Thenlookatthe patternsthat help you avoid the causes ofredesign.

6. Considerwhatshouldbevariableinyourdesign.

Thisapproachistheoppositeoffocusing on the causes of redesign. Instead of considering what might force a change to a design, consider what you want to be Able to change without redesign. The focus here is on encapsulating the concept that varies , atheme of many design patterns. Table 1.2 lists the design aspect(s) that design patterns letyouvary independently, thereby letting you change them without redesign.

How to Use aDesign Pattern

Onceyou'vepickedadesignpattern,howdoyouuseit?Here'sastep-by-stepapproachto applyingadesignpatterneffectively:

1. Read the pattern once through for an overview. Pay particular attention to the Applicability and Consequences sections to ensure the pattern is right for your problem.

2. Go back and study the Structure, Participants, and Collaborationssections.Makesureyouunderstandtheclassesandobjects inthepatternandhowtheyrelatetooneanother.

3. Look at the Sample Code section to see a concrete example of the patternincode. Studying the code helps you learn how to implement the pattern.

4. Choose names for pattern participants that are meaningful in the application context .The names for participants in design patterns are usually too abstract to appear directly in an application. Nevertheless, it's useful to

incorporate the participant name into the name that appears in the application. That helps make the pattern more explicit in the implementation. For example, if you use the Strategy pattern for a text compositing algorithm, then you might have classes Simple Layout Strategy or TeXt Layout Strategy.

5. Define the classes.Declare their interfaces, establish their inheritance relationships, and define the instance variables that represent data and object references.Identifyexistingclasses your application that the pattern will affect, and modify the maccordingly.

6. Define application-specific names for operations in the pattern. Here again then ames generally depend on the application. Use the

responsibilities and collaborations associated with each operation as aguide. Also, be consistent in your naming conventions. For example, you might use the "Create-" prefix consistently to denote a factory method

7. Implement the operations to carry out the responsibilities and collaborations in the pattern .The Implementation section offers

hints to guide you in the implementation. The examples in the Sample Code section can help as well.

Software design pattern

In software engineering, a design pattern is a general reusable solution to a commonly occurring problem within a given context in software design. A design pattern is not a finished design that can be transformed directly into code. It is a description or template for how to solve a problem that can be used in many different situations. So patterns are formalized best practices that you must implement yourself in your application.^[11]Object-oriented design patterns typically show relationships and interactions betweenclassesor objects, without specifying the final application classes or objects that are involved. Many patterns imply object-orientation or more generally mutable state, and so may not be as applicable in functional programming languages, in which data is immutable or treated assuch.

Design patterns reside in the domain of modules and interconnections. At a higher level there arearchitectural patterns that are larger in scope, usually describing an overall pattern followed

There are many types of design patterns, like by an entire system.^[2]

- Algorithm strategy patterns addressing concerns related to high-level strategies describing how to exploit application characteristics on a computing platform.
- Computationaldesignpatternsaddressingconcernsrelatedtokeycomputationidentification.
- Executionpatternsthataddressconcernsrelatedtosupportingapplicationexecution, including strategies in executing streams of tasks and building blocks to support tasksynchronization.
- Implementationstrategypatternsaddressingconcernsrelatedtoimplementingsourcecode tosupport
 - 1. program organization, and
 - 2. the common data structures specific to parallelprogramming.
- Structuraldesignpatternsaddressingconcernsrelatedtohigh-levelstructuresofapplications beingdeveloped.

<u>Design patterns</u>were originally grouped into the categories:

<u>creational patterns</u>, <u>structural patterns</u>, and <u>behavioral patterns</u>, and described using the concepts of <u>delegation, aggregation</u>, and <u>consultation</u>. For further background on object-oriented design,

see<u>coupling</u> and <u>cohesion</u>, <u>inheritance</u>, <u>interface</u>, and <u>polymorphism</u>. Another classification has also introduced the notion of <u>architectural design pattern</u> that may be applied at the architecture level of the software such as the <u>Model–View–Controller</u> pattern.

Creational pattern

In software engineering, creational design patterns are design patterns that deal with objectcreation mechanisms, trying to create objects in a manner suitable to the situation. The basic form of object creation could result in design problems or added complexity to the design. Creational design patterns solve this problem by somehow controlling this object creation.

Creational design patterns are composed of two dominant ideas. One is encapsulating knowledge about which concrete classes the system use. Another is hiding how instances of these concrete classes are created and combined.^[1]

Creational design patterns are further categorized into Object-creational patterns and Classcreational patterns, where Object-creational patterns deal with Object creation and Classcreational patterns deal with Class-instantiation. In greater details, Object-creational patterns defer part of its object creation to another object, while Class-creational patterns defer its objection creation to subclasses.^[2]

Five well-known design patterns that are parts creational patterns are:

- Abstract factory pattern, which provides an interface for creating related or dependent objects without specifying the objects' concreteclasses.
- Factory method pattern, which allows a class to defer instantiation to subclasses.
- Builder pattern, which separates the construction of a complex object from its representation so that the same construction process can create different representation.
- Prototype pattern, which specifies the kind of object to create using a prototypical instance, and creates new objects by cloning thisprototype.
- Singleton pattern. which ensures a class only has one instance, and provides a global point of access toit.

The abstract factory pattern is a software <u>design pattern</u>that provides a way to encapsulate a group of individual <u>factories</u>that have a common theme. In normal usage, the client software creates a concrete implementation of the abstract factory and then uses the generic <u>interfaces</u>to create the concrete <u>objects</u>that are part of the theme. The<u>client</u>does not know (or care) which concrete objects it gets from each of these internal factories, since it uses only the generic interfaces of their products. This pattern separates the details of implementation of a set of objects from their general usage.

The factory method pattern is an <u>object-oriented design pattern</u>to implement the concept of<u>factories</u>. Like other<u>creational patterns</u>, it deals with the problem of creating <u>objects</u>(products) without specifying the exact <u>class</u>of object that will be created. The essence of the Factory method Pattern is to "Define an interface for creating an object, but let the classes that implement the interface decide which class to instantiate. The Factory method lets a class defer instantiation to subclasses.

Thebuilderpatternisan<u>objectcreation</u>software<u>designpattern</u>. Theintentionistoabstractsteps of construction of objects so that different implementations of these steps can construct different representations of objects. Often, the builder pattern is used to build products in accordance with the <u>compositepattern</u>.

Theprototypepatternisacreationaldesignpatternusedinsoftwaredevelopmentwhenthetype of objects to create is determined by a prototypical instance, which is cloned to produce new objects. This pattern is used to:

- avoidsubclasses of an object creator in the client application, like the abstract factory patterndoes.
- avoid the inherent cost of creating a new object in the standard way (e.g., using the 'new' keyword) when it is prohibitively expensive for a givenapplication.

In<u>softwareengineering</u>, the singlet on pattern is a <u>design pattern</u> that restricts the <u>instantiation</u> of a class to one <u>object</u>. This is useful when exactly one object is needed to coordinate actions across the system. The concept is sometimes generalized to systems that operate more efficiently when only one object exists, or that restrict the instantiation to a certain number of objects. The terms comes from the <u>mathematical concept of a singleton</u>.

| Creational patterns | | | | | | | |
|----------------------------|--|--|--|-------|--|--|--|
| Name | Description | In <u>DesignPa</u> <u>tterns</u> | In <u>Code</u> Complete ^[17] | Other | | | |
| <u>Abstract</u> factory | Provide an interface for creating families of related or dependent objects without specifying their concrete classes. | Yes | Yes | N/A | | | |
| <u>Builder</u> | Separate the construction of a complex object from its representation allowing the same construction process to create various | Yes | No | N/A | | | |

| | representations. | | | |
|---|---|-----|-----|-----------------------------|
| <u>Factory</u> method | Define an interface for creating an object, but let subclasses decide which class to instantiate. Factory Method lets a class defer instantiation to subclasses (dependency injection ^[18]). | Yes | Yes | N/A |
| <u>Lazyinitial</u> <u>ization</u> | Tactic of delaying the creation of an object, the calculation of a value, or some other expensive process until the first time it is needed. | No | No | <u>PoEAA^{[19}]</u> |
| <u>Multiton</u> | Ensure a class has only named instances, and provide global point of access to them. | No | No | N/A |
| <u>Object pool</u> | Avoid expensive acquisition and release of resources by recycling objects that are no longer in use. Can be considered a generalisation of <u>connection</u> <u>pool</u> and <u>thread pool</u> patterns. | No | No | N/A |
| <u>Prototype</u> | Specify the kinds of objects to create using a prototypical instance, and create new objects by copying this prototype. | Yes | No | N/A |
| <u>Resourceac</u> <u>quisition</u> <u>isinitializati</u> <u>on</u> | Ensure that resources are properly released by tying them to the lifespan of suitable objects. | No | No | N/A |
| <u>Singleton</u> | Ensure a class has only one instance, and provide a global point of access to it. | Yes | Yes | N/A |